

Inswing Door (3" Stile)

1 Panel With

MO (mm)	2-1 15/16 (659)	2-7 15/16 (811)	2-9 15/16 (862)	3-1 15/16 (964)	3-7 15/16 (1116)
RO (mm)	2-2 7/16 (672)	2-8 7/16 (824)	2-10 7/16 (875)	3-2 7/16 (976)	3-8 7/16 (1129)
FS (mm)	2-1 7/16 (646)	2-7 7/16 (799)	2-9 7/16 (849)	3-1 7/16 (951)	3-7 7/16 (1103)
DLO (mm)	1-5 3/32 (434)	1-11 3/32 (587)	2-1 3/32 (637)	2-5 3/32 (739)	2-11 3/32 (891)

6-10 1/4 (2089)					
	UOD 2068	UOD 2668	UOD 2868	UOD 3068	UOD 3668
7-2 1/4 (2191)					
	UOD 2070	UOD 2670	UOD 2870	UOD 3070	UOD 3670
8-2 1/4 (2496)					
	UOD 2080	UOD 2680	UOD 2880	UOD 3080	UOD 3680
9-2 1/4 (2800)					
	UOD 2090	UOD 2690	UOD 2890	UOD 3090	UOD 3690
10-2 1/4 (3105)					
	UOD 20100	UOD 26100	UOD 28100	UOD 30100	UOD 36100

R = Retro Size

- All glass is tempered.
- 6 9/16" jambs required for Inswing French Door G2 and Inswing French Door 2 1/4" G2
- Doors above CN 8/0 height use 2 1/4" panels.
- Some configurations require KD.

Details and Elevations not to scale.

Please consult your local Marvin representative for additional mulling configurations.


























Please consult your local Marvin representative for masonry openings that include casings and subsills.

For further details and drawings visit the 'Technical Specifications' section at Marvin.com.

Inswing Door (3" Stile)

2 Panel Width

MO (mm)	4-1 1/8 (1248)	5-1 1/8 (1553)	5-5 1/8 (1654)	6-1 1/8 (1857)	7-1 1/8 (2162)
RO (mm)	4-1 5/8 (1260)	5-1 5/8 (1565)	5-5 5/8 (1667)	6-1 5/8 (1870)	7-1 5/8 (2175)
FS (mm)	4-0 5/8 (1235)	5-0 5/8 (1540)	5-4 5/8 (1641)	6-0 5/8 (1845)	7-0 5/8 (2149)
DLO (mm)	1-5 3/32 (434)	1-11 3/32 (587)	2-1 3/32 (637)	2-5 3/32 (739)	2-11 3/32 (891)

6-10 1/4 (2089) 6-10 1/2 (2096) 6-10 (2083) 6-1 9/64 (1682)	 UOD 4068	 UOD 5068	 UOD 5468	 UOD 6068	 UOD 7068
7-2 1/4 (2191) 7-2 1/2 (2197) 7-2 (2184) 6-5 9/64 (1784)	 UOD 4070	 UOD 5070	 UOD 5470	 UOD 6070	 UOD 7070
8-2 1/4 (2496) 8-2 1/2 (2502) 8-2 (2489) 7-5 9/64 (2089)	 UOD 4080	 UOD 5080	 UOD 5480	 UOD 6080	 UOD 7080
9-2 1/4 (2800) 9-2 1/2 (2807) 9-2 (2794) 8-5 9/64 (2394)	 UOD 4090	 UOD 5090	 UOD 5490	 UOD 6090	 UOD 7090
10-2 1/4 (3105) 10-2 1/2 (3112) 10-2 (3099) 9-5 9/64 (2698)	 UOD 40100	 UOD 50100	 UOD 54100	 UOD 60100	 UOD 70100

R = Retro Size

- All glass is tempered.
- 6 9/16" jambs required for Inswing French Door G2 and Inswing French Door 2 1/4" G2
- Doors above CN 8/0 height use 2 1/4" panels.
- Some configurations require KD.

Details and Elevations not to scale.

Please consult your local Marvin representative for additional mulling configurations.
























Please consult your local Marvin representative for masonry openings that include casings and subsills.

For further details and drawings visit the 'Technical Specifications' section at Marvin.com.

Inswing Door (3" Stile)

3 Panel With

MO (mm)	6-0 5/16 (1837)	7-6 5/16 (2294)	8-0 5/16 (2446)	9-0 5/16 (2751)	10-6 5/16 (3208)
RO (mm)	6-0 13/16 (1849)	7-6 13/16 (2307)	8-0 13/16 (2459)	9-0 13/16 (2764)	10-6 13/16 (3221)
FS (mm)	5-11 13/16 (1824)	7-5 13/16 (2281)	7-11 13/16 (2434)	8-11 13/16 (2738)	10-5 13/16 (3196)
DLO (mm)	1-5 3/32 (434)	1-11 3/32 (587)	2-1 3/32 (637)	2-5 3/32 (739)	2-11 3/32 (891)

6-10 1/4 (2089)					
	UOD 6068	UOD 7668	UOD 8068	UOD 9068	UOD 10668
6-10 1/2 (2096)					
	UOD 6070	UOD 7670	UOD 8070	UOD 9070	UOD 10670
6-10 (2083)					
	UOD 6080	UOD 7680	UOD 8080	UOD 9080	UOD 10680
6-1 9/64 (1682)					
	UOD 6090	UOD 7690	UOD 8090	UOD 9090	UOD 10690
7-2 1/4 (2191)					
	UOD 60100	UOD 76100	UOD 80100	UOD 90100	UOD 106100
7-2 1/2 (2197)					
7-2 (2184)					
6-5 9/64 (1784)					
8-2 1/4 (2496)					
8-2 1/2 (2502)					
8-2 (2489)					
7-5 9/64 (2089)					
9-2 1/4 (2800)					
9-2 1/2 (2807)					
9-2 (2794)					
8-5 9/64 (2394)					
10-2 1/4 (3105)					
10-2 1/2 (3112)					
10-2 (3099)					
9-5 9/64 (2698)					

R = Retro Size

- All glass is tempered.
- 6 9/16" jambs required for Inswing French Door G2 and Inswing French Door 2 1/4" G2
- Doors above CN 8/0 height use 2 1/4" panels.
- Some configurations require KD.

Details and Elevations not to scale.

Please consult your local Marvin representative for additional mulling configurations.

















Please consult your local Marvin representative for masonry openings that include casings and subsills.

For further details and drawings visit the 'Technical Specifications' section at Marvin.com.

Inswing Door (3" Stile)

4 Panel Width

MO (mm)	7-11 1/2 (2426)	9-11 1/2 (3035)	10-7 1/2 (3239)	11-11 1/2 (3645)
RO (mm)	8-0 (2438)	10-0 (3048)	10-8 (3251)	12-0 (3658)
FS (mm)	7-11 (2413)	9-11 (3023)	10-7 (3226)	11-11 (3632)
DLO (mm)	1-5 3/32 (434)	1-11 3/32 (587)	2-1 3/32 (637)	2-5 3/32 (739)

6-10 1/4 (2089) 6-10 1/2 (2096) 6-10 (2083) 6-1 9/64 (1682)	 UOD 8068	 UOD 10068	 UOD 10868	 UOD 12068
7-2 1/4 (2191) 7-2 1/2 (2197) 7-2 (2184) 6-5 9/64 (1784)	 UOD 8070	 UOD 10070	 UOD 10870	 UOD 12070
8-2 1/4 (2496) 8-2 1/2 (2502) 8-2 (2489) 7-5 9/64 (2089)	 UOD 8080	 UOD 10080	 UOD 10880	 UOD 12080
9-2 1/4 (2800) 9-2 1/2 (2807) 9-2 (2794) 8-5 9/64 (2394)	 UOD 8090	 UOD 10090	 UOD 10890	 UOD 12090
10-2 1/4 (3105) 10-2 1/2 (3112) 10-2 (3099) 9-5 9/64 (2698)	 UOD 80100	 UOD 100100	 UOD 108100	 UOD 120100

R = Retro Size

- All glass is tempered.
- 6 9/16" jamba required for Inswing French Door G2 and Inswing French Door 2 1/4" G2
- Doors above CN 8/0 height use 2 1/4" panels.
- Some configurations require KD.

Details and Elevations not to scale.

Please consult your local Marvin representative for additional mulling configurations.






Please consult your local Marvin representative for masonry openings that include casings and subsills.

For further details and drawings visit the 'Technical Specifications' section at Marvin.com.

Inswing Door (3" Stile)

4 Panel Width

MO (mm)	13-11 1/2 (4255)
RO (mm)	14-0 (4267)
FS (mm)	13-11 (4242)
DLO (mm)	2-11 3/32 (891)

6-10 1/4 (2089)	6-10 1/2 (2096)	6-10 (2083)	6-1 9/64 (1682)		UOD 14068
7-2 1/4 (2191)	7-2 1/2 (2197)	7-2 (2184)	6-5 9/64 (1784)		UOD 14070
8-2 1/4 (2496)	8-2 1/2 (2502)	8-2 (2489)	7-5 9/64 (2089)		UOD 14080
9-2 1/4 (2800)	9-2 1/2 (2807)	9-2 (2794)	8-5 9/64 (2394)		UOD 14090
10-2 1/4 (3105)	10-2 1/2 (3112)	10-2 (3099)	9-5 9/64 (2698)		UOD 140100

R = Retro Size

- All glass is tempered.
- 6 9/16" jambs required for Inswing French Door G2 and Inswing French Door 2 1/4" G2
- Doors above CN 8/0 height use 2 1/4" panels.
- Some configurations require KD.

Details and Elevations not to scale.

Please consult your local Marvin representative for additional mulling configurations.

Please consult your local Marvin representative for masonry openings that include casings and subsills.

For further details and drawings visit the 'Technical Specifications' section at Marvin.com.